Syropy AI Connectivity

1301nm optical module





1301nm optical module



1301nm DFB Butterfly laser module 100mW

This MQW DFB laser features high output power,good Side Mode Suppression Ratio (SMSR) and a builtin thermoelectric cooler,thermistor,and rear-faced monitor photodiode for external optical power

Optical Transceivers Introduction

With the closer between single-mode and multimode SFP optical module in recent years, the use of single-mode fiber and single-mode module has become the





Customized 100BASE-FX SFP 1310nm 2km DOM Duplex LC MMF

The SFP transceiver supports up to 2km link lengths over multi-mode fibre (MMF) using a wavelength of 1310nm. Each SFP transceiver module is individually tested to be used on a series of Cisco

50Gbps QSFP28 Optical Module

Table 1-3246 50Gbps-QSFP28-SMF-1295.56~130 0.05nm-80km-commercial specifications






Everything You Need to Know About 1310nm Optical

A 1310nm optical module lets you move data efficiently through fiber optic communication networks. As part of the O-band (1260-1360 nm), it

Optical Module, Model 130

Models 130 provide operating capabilities unavailable from other 1310nm optical sources. Among them, repetition rates to 100 MHz and precision control of amplitude and time domain.






10GHz Directly Modulated Laser Module, 1550 or

The package contains a high-speed DFB laser chip, thermoelectric cooler, thermistor, optical isolator, and a rear-facet monitor photodiode for external

Single Mode SFP Transceiver: Complete Guide Explained

Definition of a Single Mode SFP Transceiver A single mode SFP transceiver is a hot-swappable optical module designed to transmit and receive data over single mode fiber (SMF). It is commonly used in





1310nm DFB Laser Module for Analog RF application

The 1310nm DFB laser modules are intended for use in the transmission of broadband analog signals. Their high linearity makes them especially suitable for CATV broadcast and narrowcast applications.

Optical SFP Transceiver Module

Description The SFP transceivers are high performance, cost effective modules supporting data-rate of 1.25Gbps and 20km transmission distance with SMF. The






PCV1301

The PCV1301 from Foctek Photonics is a Optical Lens with Wavelength Range 1301 nm, Focal Length -25 mm, Center Thickness 2 mm, Diameter 25.4 mm, Radius 12.97 mm.

Modified uni-travelling-carrier photodiodes with 206 GHz

A uni-travelling-carrier photodiode with 206-GHz bandwidth, bandwidth-efficiency product surpassing 130 GHz and external responsivity of 0.81 A W-1 is demonstrated. Radio





optical transceiver sfp+ 10g single mode module 1310nm 10km lc

The 1310nm LC Interface 10G Singlemode Dual-fiber Optical Module is the workhorse of the modern network. It combines speed, distance, and reliability into a compact package.

SFP-1310NM-1000BASE-LX-C ATGBICS , Fiber Optic Transceiver

SFP-1310NM-1000BASE-LX-C - Transceiver Module Networking, General Purpose 1000Mbps 1310nm 3.3V LC Duplex Pluggable, SFP from ATGBICS. View datasheets, pricing and availability from





SMF 1301nm SFP Transceiver Module 40G QSFP+ AOI

High quality SMF 1301nm SFP Transceiver Module 40G QSFP+ AOI AQOLBCQ4EDMA0878 from China, China's leading product market SMF

What Is 10GBASE-LR? SMF 1310nm 10km SFP+ Explained

10GBASE-LR is a 10-gigabit Ethernet optical standard that operates at 1310 nm over single-mode fiber (SMF), supporting link distances of up to 10 km.





40Gb/s QSFP+ Transceiver

40Gb/s QSFP+ Transceiver DESIGNED FOR USE IN 40 GIGABIT ETHERNET APPLICATIONS. COMPLIANT WITH THE QSFP MSA AND IEEE 802.3BA Amphenol provides a series of 40G

1301 nm Semiconductor Optical Amplifiers (SOA), Innolume

Customized 1301 nm Semiconductor Optical Amplifiers (SOA) engineered for your needs. High stability, wavelength precision, and full in-house production ensure top performance and flexibility across all





Micro Optics for Fiber Communications

Broadcom offers Micro Lenses and integrated passive optical components for single mode (1310nm) and multi-mode (850nm) optical transceivers, optical sub-assemblies (OSA) and Active Optical Cables

Technical Characteristics Of 10G Optical Modules With

There are three wavelength windows for 10G optical module communication applications, namely the 850nm window, 1310nm window, and






SLD 1301-100R 1310nm SLD Diode Module World Class Opto

World Class Opto-Electronic Components OTDR Instruments o Spectroscopy o Optical and LOS Sensors o Optical Test Equipment Fiber Optic Instruments

1.25G 1310nm 20KM 40km sfp optical transceiver sfp

The SFP-BIDI transceivers are high performance, cost effective modules supporting data-rate of1.25Gbps and20km transmission distance with SMF.The transceiver





1310nm Single Mode Fiber Optical Transceivers Explained

A 1310nm single mode fiber optical transceiver is one of the most widely used optical transceivers in modern fiber-optic networks, especially for short-to-medium distance transmission over single-mode

Applications of 1310nm Optical Modules in Modern Networks

Conclusion 1310nm optical modules remain a workhorse technology in networking--ideal for mid-range applications such as data center links, metro networks, enterprise access, and





Ethernet Converter to Optical Fiber JetCon 1301-mw by

KORENIX JetCon 1301-mw, Korenix Industrial Compact 10/100Base-TX to 100-FX Media Rail Converter, 36-60 VDC Input, Multi Mode (2km), SC Connector,

Original AOI AQOLBCQ4EDMA0878 40G 1301nm LR4 Lite 2km

Other attributes Model Number AQOLBCQ4EDMA0878 Place of Origin Guangdong, China Brand Name AOI Use FTTX Warranty Time 1year Rate 40G Wavelength CWDM4 Distance 2km Voltage supply



Contact Us

For datasheets, pricing, or custom high-speed optical interconnect solutions, please visit:
https://syropy.com.pl